

## HuddleCamHD

### Compatibility

- VISCA Protocol
- PELCO-D
- PELCO-P

### What's in the box?

- Three-Axis Joystick
- RS232 cable
- DC12V Power Supply
- User Manual

### Features

- Durable Metal Housing
- RS232, RS485, & RS422
- On Screen Display Menu control
- Variable Pan, Tilt, Zoom, & Focus speed control
- Iris, Focus, & Preset control
- 6) Camera Quick Select keys
- 9) Quick Preset Set & Call keys

Model Number: HC-JOY-G3

Easy pan, tilt, & zoom control for any VISCA or PELCO protocol camera!  
Adjust pan, tilt, zoom, & focus speeds.  
Use 3-dimensional joystick with "twist" for zoom control



#### 1. LCD Display

Menu options are displayed here

#### 2. Lens Control

Focus+/-, Focus Lock/Unlock, Iris +/-, Auto Focus & Exposure

#### 3. Joystick

Three-axis joystick controller

#### 4. Camera Quick Select

Quickly swap between first 6 cameras

#### 5. Preset & OSD Control

Allows for preset, speed, & OSD control

#### 6. Numeric Keys

Numeric keys for presets, changing parameters, and more

#### 7. DB9 Connection

Allows for RS232 through DB9 connections

#### 8. Phoenix Connection

Allows for RS422 or RS485 wiring connections

#### 9. Power Connection

DC12V Power Connection

### Key Technical Specifications

Connections:	RS232, RS485, RS422
Baud Rate:	1200-19200 bps
Interfaces:	DB9: RS232; 5SCT: RS485/RS422
Max Cameras:	Control up to 255 Cameras
Max Presets:	Up to 255 Presets
Max Distance:	3,937' (1200m) using 24 gauge twisted pair

### Operation Specifications

Power:	6W (12VDC Voltage)
Working Temp:	14° ~ 122° F (-10° ~ +50° C)
Working Humidity:	10 ~ 90% (non-condensation)
Weight:	3.4 lbs   1.6 kg
Dimensions (in.):	12.6W x 4.3H x 7.1D
Dimensions (mm.):	320W x 109H x 180D