




Introducing the Video Collaboration Solution Team Kit

This entry level web conference kit includes equipment for high quality video conferencing and collaboration for small teams.

MSRP: \$2,024

SKU: HC-TEAMPLUS-VCS-G2-NOPC



Conferencing



Collaboration



Integration



Installation Ready

WHAT'S INCLUDED

Included with every HuddleCamHD Team+ Kit includes a 1080p 10X optical zoom USB conference camera and a HuddlePod Air Microphone / Speaker combo.

Quick Launch PE is a meeting room dashboard software allowing your team to customize the meeting room experience and lock down the PC.

**QUICK
LAUNCH**

HuddleCamHD 10X G3



HuddlePod Air



152 Robbins Rd, Downingtown, PA USA
www.HuddleCamHD.com



PC RECOMMENDATION DELL OPTIPLEX 3070

Details


Computer	i5 processor, 256 GB SSD, 8GB
Operating System	Windows 10
Camera	10X Optical Zoom 1080p Camera
Microphone	Acoustic Magic Voice Tracker II
Wall Mount	Included (camera & computer)
Cabling	6' HDMI Cable
Additional	Microsoft Wireless Keyboard/Mouse

* PC, LCD, & LCD mount not included with system.

ONE SYSTEM FOR ANY SOFTWARE


Quicklaunch is an easy-to-use multi-platform, one-click/one-touch application to join meetings, start applications, access data, play media, showcase your organization's content and business intelligence assets. It's included in both of our VCS kits for an easy to manage conference space.

QUICKLAUNCH BENEFITS



Enhance Productivity

- ▶ Simplify the complicated collaboration experience with easy to use "one click" application launching.
- ▶ Customize your meeting workspace
- ▶ Consistent and easy user experience
- ▶ Use in open or locked down modes.



Open Platform

- ▶ Easy integration with the leading video conferencing software including: Bluejeans, Vidyo, Skype and GoToMeeting.
- ▶ Easily switch between the persistent toolbar and desktop view with customized and tiered buttons
- ▶ Always in the state you expect with your organization's look and feel.



Safe, Secure & Manageable

- ▶ For IT departments, it reduces training and support cost by providing a secure and manageable interface.
- ▶ Keep your confidential data secure with the 'Room Reset' feature
- ▶ Optional 'lock-down' mode to restrict usage of your Quicklaunch device and protect it against unwanted changes.


HuddleCamHD 10X Gen3 Conferencing Camera

The HuddleCamHD 10X is ideal for small to medium sized meeting rooms. Comes standard with a certified SONY lens.

Model Number:
HC10X-GY-G3 (Black)
HC10X-WH-G3(White)
<https://huddlecamed.com/10x-q3/>

KEY FEATURES

- 10X Optical Zoom
- USB 3.0 (requires quad-core processor)
- USB 2.0 (Reduced FPS)
- RS-232
- 1920 x 1080
- 61° Field of View
- Up to 30 fps
- 64 Presets
- IR Remote



WHAT'S IN THE BOX

- 10X Zoom USB 3.0 Camera
- 12V/2.0A DC Power Adapter
- Installation Bracket & Screw
- USB 3.0 Data Cable (3m)
- Serial Control Cable
- RS-232C to RS-485 Adaptor
- IR Remote Control
- User Manual
(also available online)



1. Lens

10x Optical Zoom

2. IR Receiver

To receive IR remote controller signal

3. Power LED

Blue LED lights when unit is powered and is dark in standby mode.

4. Standby LED

Orange LED blinks for Stand-By status

5. USB 3.0 Interface

For connection to PC USB 3.0 port (also compatible w/ USB 2.0 port & driver)

6. IR Select Switch

Control up to 3 cameras through a single IR remote

7. VISCA IN Port

Used for connecting hard-wired joystick for camera control

8. VISCA OUT Port/RS-485

Used for daisy chaining multiple units in a succession with a hard wired joystick for camera control

9. DC In 12V Socket

Only use the power adapter supplied with this camera

Image Sensor & Lens

Video CMOS Sensor	1/2.8" CMOS, 2.1 Mega Pixel
Resolution	1080p-30/25, 720p-30/25
Frame Rate	up to 30fps (MJPEG)
Lens Zoom	10X Optical Zoom f=4.7-47mm
Field of View	8° (tele) to 61° (wide)

Pan/Tilt Movement

Pan Movement	±340°
Tilt Rotation	Up: 90°, Down: 30°
Presets	64 Presets

Electrical Index

Power Supply Adapter	12V DC 2A
Input Voltage	12V DC (10.5-14V DC)
Input Power	24W (Max)
Working Environment	Indoor

Other

Mfg. Warranty	2 Years Parts & Labor
---------------	-----------------------

Physical

Material	Aluminum, Plastic
Dimensions (in.)	5.7W x 6.3H x 6.0D (7.4H max w/ tilt)
Dimensions (mm)	145 x 160 x 151 (188H max w/ tilt)
Weight	2.4 lbs (1.1 kg)
Box Dimensions	12.1"W x 9.5"H x 9.6"D (307mm x 241mm x 244mm)
Boxed Weight	5.6 lbs (2.54 kg)
Operating Temperature	32°F to 113°F (0°C to 45°C)
Colors	Gray, White

Rear Board Connectors

Video Interface	USB 3.0
Controller Signal Interface	Mini DIN-8 (VISCA IN/OUT, PELCO-D IN/OUT)
Controller Signal Config.	Dip-Switch Pin 6/TTL Signal
Baud Rate	9600 bps
Power Supply Interface	DC 12V 2A


Quality Management System

QMS	Certified ISO9001: 2008
-----	-------------------------

Compatibility

- | | | | |
|----------------------|-----------------------------|-------------------------|--|
| • Windows 7/8/8.1/10 | • Easy Meeting | • Polycom Real Presence | • Google Hangouts on Air |
| • Mac OSX | • Facetime | • Radavision | • YouTube Live |
| • Acano | • Fuzebox | • Spontania | • Any app that supports the UVC camera interface |
| • Adobe Connect | • Google Hangouts | • Skype | |
| • Blue Jeans | • GoToMeeting | • TurboMeeting US | |
| • Cisco Jabber | • Lifesize | • Vidyo | |
| • Cisco Webex* | • Skype for Business (Lync) | • Zoom.US | |
- *These apps do not support Image Flip

IR Remote Control Functionality



- Reset**
Restarts the camera and restores it to Factory Default settings. (Note: Will delete all saved settings and presets.)
- Camera Selection**
Select which Camera to control via IR: 1, 2 or 3
- Preset Positions**
1-9: Preset Positions
Set: Set a Preset Position
Clear: Clear a Preset Position
Call: Call a Preset Position
Note: If you want to set (or call) the first preset position to 1, you simply press number key "1", then press "Set" or "Call" to set (call) the position.
- Fast Zoom In/Out Control Zone**
+: Zoom In quickly
-: Zoom Out quickly
- Pan/Tilt Controller**
↑ Tilt Up
↓ Tilt Down
← Pan Left
→ Pan Right
↻ Auto Pan (through Full pan range)
- Additional Function Zone**
Model Dependent Functions
Not applicable to this model
- Power Supply Switch**
Switch for turning camera on/off (i.e. Working mode vs. Stand-By mode)
- OSD Menu Zone**
Model Dependent Functions
Not applicable to this model
- Slow Zoom In/Out Control Zone**
+: Zoom In slowly
-: Zoom Out slowly
- Focus Control Zone**
Auto: Turn on Auto Focus
Manual: Turn on Manual Focus
Far: Set focus at a farther distance (requires Manual Focus)
Near: Set focus at a nearer distance (requires Manual Focus)
- Pan/Tilt Function Zone**
Home: Go to camera's Home position
Rev: Enable image flip for ceiling mounting
L-Limit: Sets left limit for Scan feature
R-Limit: Sets right limit for Scan feature
Scan: Auto pan to L&R limits
Tour: Auto tour of all saved presets

PC Recommendation

Online link:

pcpartpicker.com/list/QR62BZ

Main Features

- 9th Generation Intel i5 Processor
- 250GB SSD
- Windows 10
- 16GB (2x 8GB) DDR4 RAM



PC Parts

CPU	Intel Core i5-9600K 3.7 GHz 6-Core Processor
Motherboard	ASRock B365M Pro4 Micro ATX LGA1151 Motherboard
Memory	Corsair Vengeance LPX 16GB (2x 8GB) DDR4-2400 Memory
Storage	Samsung 970 Evo Plus 250GB M.2-2280 NVME SSD
Case	Silverstone GD09B HTPC Case
Power Supply	Silverstone 300 W 80+ Bronze Certified SFX Power Supply
Operating System	Windows 10



Compatibility

- Windows 7/8.1/10
- Mac OS X
- Acano
- Adobe Connect
- BlueJeans
- Cisco Jabber
- Cisco WebEx
- Easymeeting
- Facetime
- Fuzebox
- Google Hangouts
- GoToMeeting
- Lifesize
- Skype for Business(Lync)
- Polycom RealPresence
- Radavision
- Spontania
- Skype
- TurboMeeting.US
- Vidyo
- VSee
- Zoom.US
- Google Hangouts on Air
- YouTube Live

Features

- 2.4 GHz Wireless
- Echo Cancellation
- Noise Cancellation
- 360° omnidirectional pickup
- Full Duplex
- Easy to use
- Auto Level Control
- Neoprene Travel Case

Model Number: HP-AIR-BK
HP-AIR-WH

The HuddlePod Air is the ideal wireless speakerphone with an easy & reliable wireless connection.



What's in the Box

- HuddlePod Air Speakerphone
- Wireless Receiver & Antenna
- Neoprene Travel Case
- User Manual
- USB 2.0 Cable (charge & power)
- USB Charger

- Power LEDs**
Blue power on
- Speaker LED**
Solid Blue: Mute
Blinking Blue: Max Volume
- Volume Mute**
Mute speakerphone volume
- Power**
Turn speakerphone on/off
- Volume Up/Down**
Controls speaker volume
- Mute Microphone**
Mutes microphone
- Mic LED**
Blue: Muted
Blinking Orange: Low battery
Solid Orange: Full charge
- USB 2.0 Plug**
For power and charging
- 3.5mm Audio Jack**
For connected headphones or similar devices
- Durable Wireless Receiver**
In protective plastic case

Specifications

Microphone Features

Echo Cancellation	256 ms echo cancellation
Audio Output	1/8" TRS headphone
Noise Cancellation	Intelligent NC up to 16db
Digital Equalizer	Built-in Digital EQ for stable audio
Battery Life	6-8 Hours, 4-5 hour charge time
Warranty	3 Years

Wireless Speakerphone Specifications


Weight	0.8 lbs. (0.36 kg)
Size	7" diameter, 1.5" height (177mm diameter, 38mm height)
Working Environment	Temp 0~40 °C, Humidity 20%~85%
Compatibility	MS WIN 7/8.1/10, Mac 10.5+, Android 4.4+
RF Frequency Range	2.400 GHz ~ 2.4835 GHz
Certifications	CE Mark (R & TTE Directive)

All-in-One Media Keyboard

The All-in-One Media Keyboard has a full-sized keyset and an integrated multi-touch trackpad. Type, swipe, drag, zoom, and click with ease. It has customizable media hotkeys that put the web and your favorite music, photos, and movies at your fingertips. The keyboard also has a durable liquid resistant design.

Key Features

1. Integrated multi-touch trackpad
2. Customizable media hotkeys
3. Easy access volume controls
4. Durable spill and drop resistant design
5. Wireless connectivity (USB)
6. Advanced Encryption Standard (AES) 128-Bit Encryption
7. Also works with select TVs and gaming consoles



Performance Parameters

104 key configuration (English North American)

Frequency Range: 2.1 GHz

Power: AAA alkaline batteries (included)

Battery Life: 9 months (typical)

Compliance: FCC Class B, ROHS, REACH

Encryption AES:

This keyboard features Advanced Encryption Standard (AES*) technology, which is designed to help protect your information by encrypting your keystrokes. Each keyboard is permanently paired with its receiver at the factory – no key information is ever shared over the air.

Warranty

1-year manufacturer's warranty

Physical Parameters

Keyboard L x W x H (in.) 14.4 x 5.2 x 0.76

Keyboard L x W x H (mm) 367 x 132 x 19.4

Keyboard Weight 15.3 oz (434g)

Transceiver L x W x H (in.) 0.76 x 0.51 x 0.17

Transceiver L x W x H (mm) 18.3 x 13.1 x 4.4

Transceiver Weight 0.05 oz (1.5g)

Compatibility

Operating Systems: Windows, Linux, Mac OS

Select USB HID compliant Smart TVs and gaming consoles

Wireless Connection

Up to 33 ft. (10m) range

HuddleCamHD

Small Universal Wall Mount

HuddleCamHD

Features

- Mounts directly to wall with supplied hardware
- Black or White powder coat finish provides long lasting durability
- Universally compatible with all center mount cameras
- Mounting hardware included
- 3-year warranty


Model Number: HCM-1-BK / HCM-1-WH

Compatibility

- All small based HuddleCamHD cameras
- All PTZOptics cameras
- Most small based SONY, Panasonic, Cisco, Polycom, Vaddio, etc. cameras with a 1/4-20 mounting hole.



This Universal Thin Profile Wall Mount was designed specifically for an ideal way to wall mount a camera above or below a plasma or LCD monitor. Constructed from heavy gauge steel, this mount comes with a 3-year manufacture warranty.



1. Slot for 1/4-20 machine screw
Secures camera to mount

2. Mount Base
5 11/16" wide universal metal camera tray

3. Cable Access
Convenient cable access under mount or through wall

4. Wall Mounting Holes
Precut 4 post pattern fits U.S. doublegang box.



Size & Weight

Dimensions (in.)	5-11/16W x 8-5/16D x 5-1/16H
Dimensions (mm.)	145W x 212D x 129H
Weight	1.9 lbs 0.84 kg

What's in the box

Camera Mount
Mounting Hardware: (4) Mounting Screws & Washers
(4) Drywall/Masonry Anchors
(1) Quarter Twenty bolt
(4) Device mounting screws for 2-Gang Box